


2-4-05

I PCW

Via Express Mail Label No. EV586235123US

Date: February 3, 2005

102150-17 Eisenfuhr 204-WCG



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants : Klaus TÖPFER  
Serial No. : 10/701,300  
Filed : November 4, 2003  
For : THREADING DEVICE FOR TUBULAR  
PACKAGINGS  
Art Unit : 3643  
Examiner : Richard Thomas Price, Jr.

February 3, 2005

Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

Sir:

LETTER TO THE OFFICIAL DRAFTPERSON

Submitted herewith for entry and approval are 4 sheets of corrected formal drawings (FIG. 1-4) in the above-referenced application.

With respect to the orientation of Fig. 1 (# 12 of Notice of Draftsperson's Patent Drawing Review dated 10/28/04), the Official Draftsperson's attention is respectfully drawn to 37 CFR 1.84(i), a copy of which is annexed hereto. When turned on its side, as permitted, the numbers and reference characters are, in fact, oriented in the same direction of the view.



Favorable action is respectfully solicited.

Respectfully submitted,

NORRIS, McLAUGHLIN & MARCUS, P.A.


By 

William C. Gerstenzang  
Reg. No. 27,552

WCG/tmo  
Enc. - Formal Drawings (4 sheets)  
Copy of 37 CFR 1.84(i) (2 sheets)  
875 Third Avenue, 18<sup>th</sup> Floor  
New York, NY 10022  
Phone: (212) 808-0700  
Fax: (212) 808-0844

I hereby certify that this correspondence is being deposited with the United States Postal Services as Express Mail, Label # EV586235123US in an envelope addressed to: Commissioner For Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

NORRIS, McLAUGHLIN & MARCUS, P.A.

By   
Zsuzsa Schuster

Date February 3, 2005



102150-17 Eisenfuhr 204-WCG

Applicants : Klaus TÖPFER  
Serial No. : 10/701,300  
Filed : November 4, 2003  
For : THREADING DEVICE FOR TUBULAR  
PACKAGINGS  
Art Unit : 3643  
Examiner : Richard Thomas Price, Jr.

EXPRESS MAIL CERTIFICATE

**Express Mail Mailing Label No. EV586235123US**

Date of Deposit: February 3, 2005

I hereby certify that the following items:

1. Letter to the Official Draftsman with (4) drawing sheets
2. Copy of 37 CFR 1.84(i) (2 sheets)
3. Self-Addressed Postcard

are being deposited with the United States Postal Services Express Mail Post Office to Addressee service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

NORRIS, McLAUGHLIN & MARCUS, P.A.

By

  
Zsuzsa Schuster

## CONSOLIDATED PATENT RULES

on 21.0 cm. by 29.7 cm. (DIN size A4) drawing sheets, and a sight no greater than 17.6 cm. by 24.4 cm. (6 15/16 by 9 5/8 inches) on 21.6 cm. by 27.9 cm. (8 1/2 by 11 inch) drawing sheets.

(h) *Views.* The drawing must contain as many views as necessary to show the invention. The views may be plan, elevation, section, or perspective views. Detail views of portions of elements, on a larger scale if necessary, may also be used. All views of the drawing must be grouped together and arranged on the sheet(s) without wasting space, preferably in an upright position, clearly separated from one another, and must not be included in the sheets containing the specifications, claims, or abstract. Views must not be connected by projection lines and must not contain center lines. Waveforms of electrical signals may be connected by dashed lines to show the relative timing of the waveforms.

(1) *Exploded views.* Exploded views, with the separated parts embraced by a bracket, to show the relationship or order of assembly of various parts are permissible. When an exploded view is shown in a figure which is on the same sheet as another figure, the exploded view should be placed in brackets.

(2) *Partial views.* When necessary, a view of a large machine or device in its entirety may be broken into partial views on a single sheet, or extended over several sheets if there is no loss in facility of understanding the view. Partial views drawn on separate sheets must always be capable of being linked edge to edge so that no partial view contains parts of another partial view. A smaller scale view should be included showing the whole formed by the partial views and indicating the positions of the parts shown. When a portion of a view is enlarged for magnification purposes, the view and the enlarged view must each be labeled as separate views.

(i) Where views on two or more sheets form, in effect, a single complete view, the views on the several sheets must be so arranged that the complete figure can be assembled without concealing any part of any of the views appearing on the various sheets.


(ii) A very long view may be divided into several parts placed one above the other on a single sheet. However, the relationship between the different parts must be clear and unambiguous.

(3) *Sectional views.* The plane upon which a sectional view is taken should be indicated on the view from which the section is cut by a broken line. The ends of the broken line should be designated by Arabic or Roman numerals corresponding to the view number of the sectional view, and should have arrows to indicate the direction of sight. Hatching must be used to indicate section portions of an object, and must be made by regularly spaced oblique parallel lines spaced sufficiently apart to enable the lines to be distinguished without difficulty. Hatching should not impede the clear reading of the reference characters and lead lines. If it is not possible to place reference characters outside the hatched area, the hatching may be broken off wherever reference characters are inserted. Hatching must be at a substantial angle to the surrounding axes or principal lines, preferably 45°. A cross section must be set out and drawn to show all of the materials as they are shown in the view from which the cross section was taken. The parts in cross section must show proper material(s) by hatching with regularly spaced parallel oblique strokes, the space between strokes being chosen on the basis of the total area to be hatched. The various parts of a cross section of the same item should be hatched in the same manner and should accurately and graphically indicate the nature of the material(s) that is illustrated in cross section. The hatching of juxtaposed different elements must be angled in a different way. In the case of large areas, hatching may be confined to an edging drawn around the entire inside of the outline of the area to be hatched. Different types of hatching should have different conventional meanings as regards the nature of a material seen in cross section.

(4) *Alternate position.* A moved position may be shown by a broken line superimposed upon a suitable view if this can be done without crowding; otherwise, a separate view must be used for this purpose.

(5) *Modified forms.* Modified forms of construction must be shown in separate views.

(i) *Arrangement of views.* One view must not be placed upon another or within the outline of another. All views on the same sheet should stand in the same direction and, if possible, stand so that they can be read with the sheet held in an upright position. If views wider than the width of the sheet are necessary for the clearest illustration of the invention, the



sheet may be turned on its side so that the top of the sheet, with the appropriate top margin to be used as the heading space, is on the right-hand side. Words must appear in a horizontal, left-to-right fashion when the page is either upright or turned so that the top becomes the right side, except for graphs utilizing standard scientific convention to denote the axis of abscissas (of X) and the axis of ordinates (of Y).

(j) *Front page view.* The drawing must contain as many views as necessary to show the invention. One of the views should be suitable for inclusion on the front page of the patent application publication and patent as the illustration of the invention. Views must not be connected by projection lines and must not contain center lines. Applicant may suggest a single view (by figure number) for inclusion on the front page of the patent application publication and patent.

(k) *Scale.* The scale to which a drawing is made must be large enough to show the mechanism without crowding when the drawing is reduced in size to two-thirds in reproduction. Indications such as "actual size" or "scale 1/2" on the drawings are not permitted since these lose their meaning with reproduction in a different format.

(l) *Character of lines, numbers, and letters.* All drawings must be made by a process which will give them satisfactory reproduction characteristics. Every line, number, and letter must be durable, clean, black (except for color drawings), sufficiently dense and dark, and uniformly thick and well-defined. The weight of all lines and letters must be heavy enough to permit adequate reproduction. This requirement applies to all lines however fine, to shading, and to lines representing cut surfaces in sectional views. Lines and strokes of different thicknesses may be used in the same drawing where different thicknesses have a different meaning.

(m) *Shading.* The use of shading in views is encouraged if it aids in understanding the invention and if it does not reduce legibility. Shading is used to indicate the surface or shape of spherical, cylindrical, and conical elements of an object. Flat parts may also be lightly shaded. Such shading is preferred in the case of parts shown in perspective, but not for cross sections. See paragraph (h)(3) of this section. Spaced lines for shading are preferred. These lines must be thin, as few in number as practicable, and they must contrast with the rest of the drawings. As a substitute

for shading, heavy lines on the shade side of objects can be used except where they superimpose on each other or obscure reference characters. Light should come from the upper left corner at an angle of 45°. Surface delineations should preferably be shown by proper shading. Solid black shading areas are not permitted, except when used to represent bar graphs or color.

(n) *Symbols.* Graphical drawing symbols may be used for conventional elements when appropriate. The elements for which such symbols and labeled representations are used must be adequately identified in the specification. Known devices should be illustrated by symbols which have a universally recognized conventional meaning and are generally accepted in the art. Other symbols which are not universally recognized may be used, subject to approval by the Office, if they are not likely to be confused with existing conventional symbols, and if they are readily identifiable.

(o) *Legends.* Suitable descriptive legends may be used subject to approval by the Office, or may be required by the examiner where necessary for understanding of the drawing. They should contain as few words as possible.

(p) *Numbers, letters, and reference characters.*

(1) Reference characters (numerals are preferred), sheet numbers, and view numbers must be plain and legible, and must not be used in association with brackets or inverted commas, or enclosed within outlines, e.g., encircled. They must be oriented in the same direction as the view so as to avoid having to rotate the sheet. Reference characters should be arranged to follow the profile of the object depicted.

(2) The English alphabet must be used for letters, except where another alphabet is customarily used, such as the Greek alphabet to indicate angles, wavelengths, and mathematical formulas.

(3) Numbers, letters, and reference characters must measure at least .32 cm. (1/8 inch) in height. They should not be placed in the drawing so as to interfere with its comprehension. Therefore, they should not cross or mingle with the lines. They should not be placed upon hatched or shaded surfaces. When necessary, such as indicating a surface or cross section, a reference character may be underlined and a blank space may be left in the hatching or shading where the character occurs so that it appears distinct.